

Water Reduction Reference

Supreme XTreme | Optional Step

Field note:

Many of our customers - including experienced applicators working floors, walls, and commercial surfaces - skip water reduction entirely and get excellent results.

This is a tool. Use it when it helps. Skip it when it doesn't.

What water reduction does:

- **Improves leveling:** Helps the mixed product self-level on large horizontal surfaces for a smoother finish.
- **Easier workability:** Reduces drag during application, especially over large surface areas.
- **Viscosity control:** Acts as a dial - thinner mix spreads easier; thicker holds better on vertical surfaces.
- **Extends open time:** In dry / low-humidity environments, a small amount can buy extra working time.
- **Humidity note:** High humidity = use less water. Low humidity = a bit more may help.
- **Does NOT speed cure:** Waiting after mixing does nothing. Apply right away regardless of whether you reduce.

If you choose to reduce - amounts by surface type:

	Quart	Gallon
Vertical - Clears & Colors	1 oz.	4 oz.
Horizontal - Colors	4 oz.	16 oz.
Horizontal - Clear (Normal)	5 oz.	20 oz.
Horizontal - Clear (Very Smooth)	7-8 oz.	30 oz.

Add water slowly to the mixed product and stir 1-2 minutes until fully blended. Apply immediately.